



Wyse V10L

Designed to Perform in Data-driven Environments

The Wyse Thin OS powered Wyse V10L thin computer delivers the performance you need; dual-video support (with purchase of optional monitor splitter cable); 128MB Flash, 128MB DDR RAM; plus serial, parallel, and USB ports. Using the same form-factor as the Wyse V class family of thin computers, the Wyse V10L can fit easily into most work environments.

Features	Benefits
ICA version 10.x compatibility	Allows you to connect to Citrix XenApp and take advantage of some of the latest additions (32-bit icon support, Backup PNAgent URL, etc.) as well as features not available on any other non-windows client (Speedscreen Multimedia Acceleration, Smartcard smoothing, Session Reliability, etc.)
Multiple session support with true seamless windows	Increases user productivity by enabling multiple applications to run with a fully functional and familiar user interface.
Significantly faster remote application execution performance than most thin clients	The ultra-thin and highly optimized Wyse Thin OS software achieves fast and responsive performance with modest low-cost hardware. Performance is typically up to 3x of other thin clients even those with more powerful microprocessors.
Image loading via DHCP and ftp	Permits reconfiguration, firmware upgrades, and customized configurations either from an administration server or other desktops.
Plug-and-play connectivity	Simple and fast to install, connect, and use out of the box.
USB mass storage support	Plug and play support for USB keychain drives. Supports drive mapping in ICA and RDP sessions.
Data security and integrity	No data is stored on the thin client, so it cannot be lost or stolen.
Small and compact unit	Readily fits into most any workspace, as well as "out of the way" mounting options.
No fans or disks	No motors results in lower power consumption, quiet operation, and ultra-high reliability (very high MTBF).

Technical Specifications

Processor	Via C7 Eden 800MHz
Memory	128MB Flash/128MB DDR RAM
I/O peripheral support	<ul style="list-style-type: none"> - One DVI-I Port - One DVI-I Port to VGA (DB-15) Adapter - Dual-video Support with: <ul style="list-style-type: none"> - Optional DVI-I to DVI-D plus VGA-monitor splitter cable (sold separately) - Enhanced USB keyboard with PS/2 mouse port and Windows keys - PS/2 mouse included - One serial port - One parallel port - Three USB 2.0 ports (1 on front, 2 on back)
Networking	10/100 Base-T Fast Ethernet twisted pair (RJ-45) Optional external USB 802.11b/g wireless adapter
Display	<ul style="list-style-type: none"> - VESA monitor support with Display Data Control (DDC) for automatic setting of resolution and refresh rate - Single Monitor at 32-bit color or 24-bit color: up to 1920x1200@60Hz - Dual Monitors used simultaneously (requires optional monitor splitter cable): up to 1280x1024x32bpp@60Hz
Audio	<ul style="list-style-type: none"> - Output: 1/8-inch mini, full 16-bit stereo, 48KHz sample rate - Input: 1/8-inch, 8-bit mini microphone
Options	Internal Smart Card reader Internal wireless
Physical characteristics	Height: 7.9 inches (201mm) Width: 1.8 inches (46mm) Depth: 7.1 inches (180mm) Shipping Weight: 8 lbs. (3.6kg)
Mountings	Vertical foot (optional horizontal feet) Optional VESA mounting bracket Built-in Kensington security slot (cable sold separately)
Power	Worldwide auto-sensing 100-240 VAC, 50/60 Hz Average power usage with device connected to 1 keyboard with 1 PS/2 mouse and 1 monitor: 17.2 Watts/hour
Temperature Range	Horizontal position: 50° to 95° F (10° to 35° C) Vertical position: 50° to 104° F (10° to 40° C)
Security	Kensington Lock Slot
Safety Certifications	German EKI-ITB 2000, ISO 9241-3/-8 cULus 60950, TÜV-GS, EN 60950 FCC Class B, CE, VCCI, C-Tick WEEE, RoHS Compliant
Warranty	Three-year limited warranty



Wyse Technology Inc.
 3471 North First Street
 San Jose, CA 95134-1801

Visit our website at:
<http://www.wyse.com>

Or send email to:
sales@wyse.com

Wyse Sales:
 800 GET WYSE
 (800 438 9973)

Wyse Customer
 Service Center:
 800 800 WYSE
 (800 800 9973)