



# Wyse V30LE

## Flexibility, Simplicity, and Security for Thin Computing

The high-range Wyse V30LE thin computer delivers the Windows CE performance you need; dual-video support (with purchase of optional monitor splitter cable); 128MB Flash, 128MB DDR2 RAM; a CardBus/PCMCIA slot; plus serial, parallel, and USB ports. Using the same form-factor as the Wyse V class family of thin computers, the Wyse V30LE can fit easily into most work environments.

Features	Benefits
Microsoft® Windows CE 5.0 operating system	Microsoft's most popular embedded operating system.
Support for latest Citrix ICA client (version 10.x)	Allows you to use the latest ICA features, including shared application folders, seamless windows, SpeedScreen Multimedia Acceleration, PNAgent backup URL support and automatic proxy detection.
Support internal and external 802.11b/g wireless network adapter	Connect with strong wireless authentication and encryption protocols: 802.1x Authentication EAP(TLS, PEAP, MD5-Challenge, LEAP, FAST), WPA-2, TKIP in enterprise environments.
Supports RDP 5.x, and SGD 4.2 clients	Connectivity to almost any back-end system and flexibility to choose the optimal protocol.
Ericom PowerTerm Terminal Emulation	Support for over 35 emulation types, Multiple language, and Administrative lockdown of any feature to prevent misuse.
Includes Wyse firmware enhancements	The Wyse-enhanced operating system offers security features, modular software add-ons, optional windowing, fast boot, and more.
Diskless, fanless, convection cooled	Quiet, no moving parts, durable, low operating cost, low service.

## Technical Specifications

Processor	Via C7 Eden 1.2GHz
Memory	128MB Flash/128MB DDR2 RAM
I/O peripheral support	<ul style="list-style-type: none"> <li>- One DVI-I Port</li> <li>- One DVI-I Port to VGA (DB-15) Adapter</li> <li>- Dual-video Support with: <ul style="list-style-type: none"> <li>- Optional DVI-I to DVI-D plus VGA-monitor splitter cable (sold separately)</li> </ul> </li> <li>- Enhanced USB keyboard with PS/2 mouse port and Windows keys</li> <li>- PS/2 mouse included</li> <li>- One serial port</li> <li>- One parallel port</li> <li>- Three USB 2.0 ports (1 on front, 2 on back)</li> <li>- Optional CardBus /PCMCIA card slot</li> </ul>
Networking	10/100 Base-T Fast Ethernet twisted pair (RJ-45) Optional external USB 802.11b/g wireless adapter
Display	<ul style="list-style-type: none"> <li>- VESA monitor support with Display Data Control (DDC) for automatic setting of resolution and refresh rate</li> <li>- Single Monitor at 32-bit color: up to 1920x1440</li> <li>- Dual Monitors used simultaneously (requires optional monitor splitter cable) at 32-bit color: up to 1680x1050</li> </ul>
Audio	Output: 1/8-inch mini, full 16-bit stereo, 48KHz sample rate Input: 1/8-inch, 8-bit mini microphone
Options	Internal Smart Card reader Internal wireless
Physical characteristics	Height: 7.9 inches (201mm) Width: 1.8 inches (46mm) Depth: 7.1 inches (180mm) Shipping Weight: 8 lbs. (3.6kg)
Mountings	Vertical foot (optional horizontal feet) Optional VESA mounting bracket Built-in Kensington security slot (cable sold separately)
Power	Worldwide auto-sensing 100-240 VAC, 50/60 Hz Average power usage with device connected to 1 keyboard with 1 PS/2 mouse and 1 monitor: 14.9 Watts/hour
Temperature Range	Horizontal position: 50° to 95° F (10° to 35° C) Vertical position: 50° to 104° F (10° to 40° C)
Humidity	20% to 80% noncondensing
Security	Kensington Lock Slot
Safety Certifications	German EKI-ITB 2000, ISO 9241-3/-8 cULus 60950, TÜV-GS, EN 60950 FCC Class B, CE, VCCI, C-Tick WEEE, RoHS Compliant
Warranty	Three-year limited warranty



Wyse Technology Inc.  
3471 North First Street  
San Jose, CA 95134-1801

Visit our website at:  
<http://www.wyse.com>

Or send email to:  
[sales@wyse.com](mailto:sales@wyse.com)

Wyse Sales:  
800 GET WYSE  
(800 438 9973)

Wyse Customer  
Service Center:  
800 800 WYSE  
(800 800 9973)